



SAFETY DATA SHEET

Woodstikk PRF Structural Weatherproof Kit Part B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Woodstikk PRF Structural Weatherproof Kit Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive / Sealant Catalyst.

1.3. Details of the supplier of the safety data sheet

Supplier UREKA GLOBAL LTD
7 FLOWERS HILL,
BRISLINGTON
BRISTOL
BS4 5JJ
+44 117 971 1364
sales@thenamesthatsticks.com

1.4. Emergency telephone number

Emergency telephone Ureka Global +44 (0)117 971 1364 (Mon - Fri) 09:00 - 16:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Muta. 2 - H341 Carc. 2 - H351 STOT SE 2 - H371

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H226 Flammable liquid and vapour.
H302+H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H371 May cause damage to organs .
H412 Harmful to aquatic life with long lasting effects.

Woodstikk PRF Structural Weatherproof Kit Part B

Precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe vapour/ spray.
 P261 Avoid breathing vapour/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P301+P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P310 Immediately call a POISON CENTER/ doctor.
 P321 Specific treatment (see medical advice on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P363 Wash contaminated clothing before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Formaldehyde, oligomeric reaction products with phenol., FORMALDEHYDE ...%, PHENOL, METHANOL

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Formaldehyde, oligomeric reaction products with phenol.	30-60%
CAS number: 9003-35-4	
Classification	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	

Woodstikk PRF Structural Weatherproof Kit Part B

ETHANOL 10-25%
CAS number: 64-17-5 EC number: 200-578-6 REACH registration number: 01-2119457610-43-XXXX
Classification Flam. Liq. 2 - H225
FORMALDEHYDE ...% 5-10%
CAS number: 50-00-0 EC number: 200-001-8
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335
PHENOL 1-5%
CAS number: 108-95-2 EC number: 203-632-7
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Muta. 2 - H341 STOT RE 2 - H373
METHANOL 1-5%
CAS number: 67-56-1 EC number: 200-659-6 REACH registration number: 01-2119433307-44-XXXX
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from source of contamination. Chemical burns must be treated by a physician.

Woodstikk PRF Structural Weatherproof Kit Part B

Inhalation	Get medical attention immediately. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Get medical attention immediately. Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Chemical burns must be treated by a physician.
Skin contact	Get medical attention immediately. Wash skin thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated by a physician.
Eye contact	Get medical attention immediately. Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Chemical burns must be treated by a physician.
Protection of first aiders	No action should be taken involving any personal risk without suitable training. First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Irritating to respiratory system. Coughing.
Ingestion	May cause chemical burns in mouth, oesophagus and stomach. Stomach pain.
Skin contact	Corrosive to skin and eyes. Causes burns. Pain or irritation. Redness. Blistering may occur.
Eye contact	Corrosive. Causes burns. Pain. Profuse watering of the eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	None known.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO). Oxides of nitrogen.
--------------------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	Evacuate area. No action shall be taken without appropriate training or involving any personal risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Woodstikk PRF Structural Weatherproof Kit Part B

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Avoid inhalation of vapours and spray/mists. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

For emergency responders Wear personal protective equipment as described in section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. Move containers from spillage area. Contain and absorb spillage with sand, earth or other non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Neutralise spilled material with crushed limestone, slaked lime (calcium hydroxide), soda ash (sodium carbonate) or sodium bicarbonate. The contaminated absorbent may pose the same hazard as the spilled material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin, eyes and clothing. Avoid breathing vapour/spray. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Keep container tightly sealed when not in use. Do not reuse empty containers.

Advice on general occupational hygiene Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from the following materials: Alkalis. Keep container tightly sealed when not in use. Use appropriate containment to avoid environmental contamination. Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

FORMALDEHYDE ...%

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2.5 mg/m³

Short-term exposure limit (15-minute): WEL 2 ppm 2.5 mg/m³

PHENOL

Long-term exposure limit (8-hour TWA): WEL 2 ppm(Sk)

Short-term exposure limit (15-minute): WEL

METHANOL

Woodstikk PRF Structural Weatherproof Kit Part B

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 266 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 333 mg/m³(Sk)

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear protective clothing. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible. Wear suitable coveralls to prevent exposure to the skin.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse. Provide eyewash station and safety shower.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a full facepiece respirator fitted with the following cartridge: Gas filter, type A2. Gas filter, type AX.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Dark brown.
Odour	Formaldehyde. Strong.
Odour threshold	No information available.
pH	7.0-8.0
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	35°C Pensky-Martens closed cup.
Evaporation rate	No information available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	~ 1.230 @ 25°C
Bulk density	Not available.
Solubility(ies)	Soluble in water.

Woodstikk PRF Structural Weatherproof Kit Part B

Partition coefficient	No information available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	13000-25000 mPa s @ 25°C
Explosive properties	Not available.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 25.5 %.
----------------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
---	--

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Metal compounds. Alkalis.
---------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	1,111.11
-------------------------	----------

Acute toxicity - dermal

ATE dermal (mg/kg)	3,333.33
---------------------------	----------

Acute toxicity - inhalation

ATE inhalation (gases ppm)	7,777.78
-----------------------------------	----------

ATE inhalation (vapours mg/l)	33.33
--------------------------------------	-------

ATE inhalation (dusts/mists mg/l)	5.56
--	------

Carcinogenicity

Carcinogenicity	Known human carcinogen.
------------------------	-------------------------

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Woodstikk PRF Structural Weatherproof Kit Part B

12.3. Bioaccumulative potential

Bioaccumulative potential log Pow: ≤ 0.77 , BCFss: <10 , Methanol log Pow: 0.35, BCFss: 0.396, Formaldehyde log Pow: 1.47, BCFss: 17.5, Phenol

Partition coefficient No information available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1866
UN No. (IMDG)	1866
UN No. (ICAO)	1866
UN No. (ADN)	1866

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	RESIN SOLUTION
Proper shipping name (IMDG)	RESIN SOLUTION
Proper shipping name (ICAO)	RESIN SOLUTION
Proper shipping name (ADN)	RESIN SOLUTION

14.3. Transport hazard class(es)

3

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group III

Woodstikk PRF Structural Weatherproof Kit Part B

IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	.3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (as amended) EH40/2005 Workplace exposure limits. Health and Safety at Work etc. Act 1974 (as amended). Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Issued by	Compliance Manager
Revision date	16/09/2021
Revision	1
SDS number	24702

Woodstikk PRF Structural Weatherproof Kit Part B

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H370 Causes damage to organs .
H371 May cause damage to organs .
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

DIRECTIONS FOR USE

PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.