

Pafra Adhesives Ltd Bentalls, Basildon, Essex, SS14 3BU

Telephone +44 (0) 1268 290610

Fax +44 (0) 1268 290619
Email enquiries@pafra.com
Website www.pafra.com

# AquaPAL® 5899 Padding Adhesive

Issue 6 01/04/2014

AquaPAL® 5899 is a PVA based adhesive specifically developed for the stationary market where the adhesive is applied by brush or roller. It is designed as a padding adhesive for the manufacture of notepads, being applied in two coats. The second coat is applied once the first coat is partially dry. AquaPAL® 5899 gives a flexible non-tacky bond when dry and is suitable for a variety of plain papers.

## Features & Benefits

- Excellent Flexibility
- Completely Non-tacky when dry
- Easy Clean
- Non-blocking

AquaPAL® 5899 was developed for use in food packaging, please refer to our Food Contact Status Declaration for more information.

#### **Technical Data**

 Viscosity:
 30.0 - 40.0 Poise @ 11.8 sec<sup>-1</sup>
 pH:
 5.4

 Solids:
 37.0 - 40.0% sg (20 °C)
 1.05

 Brookfield 4/20/25:
 - centiPoise
 Colour:
 White

## **Application Details**

AquaPAL® 5899 is designed for application by brush or roller. The adhesive should be applied at between 15-25 °C.

### Storage & Shelf Life

For optimum performance use within 4 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

## Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

### Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

