

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond ET5429B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond ET5429B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-component, epoxy-based adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone number CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Permabond ET5429B

Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P302+P352a IF ON SKIN: Wash with plenty of soap and water</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p>
Contains	<p>POLYAMIDOAMINE, ATBN POLYMER, 3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE), 2-PIPERAZIN-1-YLETHYLAMINE</p>
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with existing Community, National and local regulations.</p>

2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

POLYAMIDOAMINE	60-100%
CAS number: 68082-29-1 EC number: 500-191-5 REACH registration exemption – POLYMER	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	
ATBN POLYMER	10-30%
CAS number: 68683-29-4 REACH registration exemption – POLYMER	
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317	
TRIS-2,4,6-(DIMETHYLAMINOMETHYL)PHENOL	10-30%
CAS number: 90-72-2 EC number: 202-013-9 REACH registration number: 01-2119560597-27-XXXX	
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	

Permabond ET5429B

3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)	5-10%
CAS number: 4246-51-9	EC number: 224-207-2
	REACH registration number: 01-2119963377-26-XXXX
Classification	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
2-PIPERAZIN-1-YLETHYLAMINE	<1%
CAS number: 140-31-8	EC number: 205-411-0
	REACH registration number: 01-2119471486-30-XXXX
Classification	
Acute Tox. 4 - H302	
Acute Tox. 3 - H311	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Repr. 2 - H361	
STOT RE 1 - H372	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. If symptoms develop, obtain medical attention
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any contact lenses and open eyelids wide apart. Get medical attention. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Irritation of nose, throat and airway.
Ingestion	May cause chemical burns in mouth and throat.
Skin contact	Chemical burns. Mild dermatitis, allergic skin rash.
Eye contact	May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. Treat symptomatically.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Permabond ET5429B

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NO_x). Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal. Wash area with soap and water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

Storage class Corrosive storage.

7.3. Specific end use(s)

Specific end use(s) Adhesive. Sealant.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

POLYAMIDOAMINE (CAS: 68082-29-1)

DNEL	Workers - Inhalation; Long term systemic effects: 3.9 mg/m ³ Workers - Dermal; Long term systemic effects: 1.1 mg/kg/day
PNEC	Fresh water; 0.004 mg/l marine water; 0 mg/l STP; 3.84 mg/l Sediment (Freshwater); 434.02 mg/kg Sediment (Marinewater); 43.4 mg/kg

Permabond ET5429B

TRIS-2,4,6-(DIMETHYLAMINOMETHYL)PHENOL (CAS: 90-72-2)

PNEC Fresh water; 0.084 mg/l
marine water; 0.008 mg/l
STP; 0.2 mg/l

3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE) (CAS: 4246-51-9)

DNEL Workers - Inhalation; Long term systemic effects: 59 mg/m³
Workers - Inhalation; Short term systemic effects: 176 mg/m³
Workers - Inhalation; Long term local effects: 1 mg/m³
Workers - Inhalation; Short term local effects: 13 mg/m³
Workers - Dermal; Long term systemic effects: 8.3 mg/kg

PNEC Fresh water; 0.22 mg/l
marine water; 0.022 mg/l
Intermittent release; 2.2 mg/l
STP; 125 mg/l
Sediment (Freshwater); 0.809 mg/kg
Sediment (Marinewater); 0.0809 mg/kg
Soil; 0.0337 mg/kg

2-PIPERAZIN-1-YLETHYLAMINE (CAS: 140-31-8)

DNEL Workers - Inhalation; Long term systemic effects: 10.6 mg/m³
Workers - Inhalation; Short term systemic effects: 10.6 mg/m³
Workers - Inhalation; Long term local effects: 15 µg/m³
Workers - Inhalation; Short term local effects: 80 mg/m³
Workers - Dermal; Long term systemic effects: 3.33 mg/kg/day

PNEC Fresh water; 0.058 mg/l
marine water; 0.006 mg/l
STP; 250 mg/l
Sediment (Freshwater); 215 mg/kg
Sediment (Marinewater); 21.5 mg/kg
Intermittent release; 0.58 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Permabond ET5429B

Hand protection	It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
Other skin and body protection	Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.
Respiratory protection	Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Black.
Odour	Amine.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	$>100^{\circ}\text{C}$
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.0
Solubility(ies)	Slightly soluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not applicable.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	≈ 150000 mPa s @ 23°C Thixotropic

Permabond ET5429B

Explosive properties Not determined.

Oxidising properties Not applicable.

9.2. Other information

Other information Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Under normal conditions of storage and use, no hazardous reactions will occur.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Reactions with the following materials may generate heat: Epoxy resin

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Inhalation

Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

Ingestion

Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact

This product is strongly irritating. Prolonged contact may cause burns.

Eye contact

Causes serious eye damage.

Toxicological information on ingredients.

POLYAMIDOAMINE

Permabond ET5429B

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,000.1
mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.1
mg/kg)

Species Rat

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL 1000 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Not available.

ATBN POLYMER

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 15,400.0
mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,000.0
mg/kg)

Permabond ET5429B

Species	Rabbit
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	No specific test data are available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Moderately irritating. Rabbit
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Slightly irritating. Rabbit
<u>Skin sensitisation</u>	
Skin sensitisation	Sensitising. Guinea pig
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No specific test data are available.
<u>Carcinogenicity</u>	
Carcinogenicity	No specific test data are available.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No specific test data are available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No information available.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

TRIS-2,4,6-(DIMETHYLAMINOMETHYL)PHENOL

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	2,169.0
Species	Rat
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	No information available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Method: OECD 404, Rabbit Corrosive
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Rabbit Causes serious eye irritation.
<u>Skin sensitisation</u>	
Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Mild dermatitis, allergic skin rash.

Permabond ET5429B

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Genotoxicity - in vivo No information available.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL 15 mg/kg/day, Oral, Rat F1

Reproductive toxicity - development Developmental toxicity: - NOAEL: >150 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,160.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,150.0

Species Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Skin corrosion/irritation Corrosive to skin.

Serious eye damage/irritation

Serious eye damage/irritation Highly irritating.

Skin sensitisation

Skin sensitisation No information available.

Germ cell mutagenicity

Genotoxicity - in vitro Bacterial reverse mutation test: Negative.

Carcinogenicity

Carcinogenicity No information available.

Permabond ET5429B

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL 600 mg/kg/day, Oral, Rat P

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

2-PIPERAZIN-1-YLETHYLAMINE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,500.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 866.0

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Animal data Severe skin irritation. Rabbit

Serious eye damage/irritation

Serious eye damage/irritation Highly irritating. Rabbit

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEC 8000 mg/l, Oral, Rat P

Reproductive toxicity - development Developmental toxicity: - NOAEL: 75 mg/kg/day, Oral, Rabbit

Specific target organ toxicity - single exposure

Permabond ET5429B

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecological information on ingredients.

POLYAMIDOAMINE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 7.07 mg/l, Danio rerio (Zebrafish)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 24 hours: 9.72 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 4.34 mg/l, Pseudokirchneriella subcapitata
Acute toxicity - microorganisms	EC ₅₀ , 3 hours: 384 mg/l, Activated sludge

ATBN POLYMER

Acute aquatic toxicity

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: > 1000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: > 1000 mg/l, Algae

TRIS-2,4,6-(DIMETHYLAMINOMETHYL)PHENOL

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 175 mg/l, Cyprinus carpio (Common carp)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 96 hours: 718 mg/l, Palaemonetes vulgaris
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 84 mg/l, Scenedesmus subspicatus
Acute toxicity - microorganisms	NOEC, 28 days: 2 mg/l, Activated sludge

3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)

Permabond ET5429B

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: > 215 - < 464 mg/l, Leuciscus idus (Golden orfe)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 218 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: > 500 mg/l, Scenedesmus subspicatus
Acute toxicity - microorganisms	EC ₅₀ , 17 hours: 221.9 mg/l, Pseudomonas putida

2-PIPERAZIN-1-YLETHYLAMINE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: > 100 mg/l, Pimephales promelas (Fat-head Minnow) LC ₅₀ , 96 hours: 2190 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 58 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)

Biodegradation Water - Degradation 10%: < 60 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not applicable.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

Disposal methods Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Permabond ET5429B

Waste class 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

SECTION 14: Transport information

14.1. UN number

2735

14.2. UN proper shipping name

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (contains 3,3'-Oxybis(ethyleneoxy)bis(propylamine))

14.3. Transport hazard class(es)

8

Transport labels



14.4. Packing group

III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-A, S-B

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Guidance Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.
CHIP for everyone HSG228.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

Permabond ET5429B

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	09/07/2020
Revision	4
Supersedes date	29/05/2015
Hazard statements in full	H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.