

SAFETY DATA SHEET TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier QUIN GLOBAL (UK) LTD

PO BOX 7634 PERTH PH2 1GA

+44 (0)845 381 2233

technical.uk@quinglobal.com

1.4. Emergency telephone number

Emergency telephone +44 (0)845 381 2233 (Mon - Fri) 09:00 - 16:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram







Signal word Da

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Additional information For professional users only.

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, Acetone

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Dimethyl ether 30-60%

CAS number: 115-10-6 EC number: 204-065-8 REACH registration number: 01-

2119472128-37-XXXX

Classification

Flam. Gas 1 - H220 Press. Gas (Liq.) - H280

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

30-60%

CAS number: — EC number: 921-024-6 REACH registration number: 01-

2119475514-35-XXXX

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Acetone 1-5%

CAS number: 67-64-1 EC number: 200-662-2 REACH registration number: 01-

2119471330-49-XXXX

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel.

Inhalation Get medical attention immediately. Move affected person to fresh air and keep warm and at

rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Place unconscious person on their side in the recovery position and ensure breathing can

take place.

Ingestion Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Rinse nose and mouth with water. Place unconscious person on their side in the recovery position and ensure breathing can take place. Never give anything by mouth to an

unconscious person. Get medical attention.

Skin contact After contact with skin, take off immediately all contaminated clothing, and wash immediately

with plenty of water. Remove contamination with soap and water or recognised skin cleansing agent. If adhesive bonding occurs, do not force skin apart. Get medical attention if symptoms

are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for

at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Coughing, chest tightness, feeling of chest pressure. Irritation of nose, throat and airway.

Vapours may cause drowsiness and dizziness.

Ingestion Coughing, chest tightness, feeling of chest pressure. Ingestion may cause severe irritation of

the mouth, the oesophagus and the gastrointestinal tract. May cause chemical burns in

mouth, oesophagus and stomach.

Skin contactBonds skin and eyes in seconds. Causes skin irritation.

Eye contact Bonds skin and eyes in seconds. Causes serious eye irritation. Severe irritation, burning and

tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor If adhesive bonding occurs, do not force eyelids apart. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is highly flammable. Containers can burst violently or explode when heated, due

to excessive pressure build-up.

Hazardous combustion

products

Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Evacuate area. Stop leak if safe to do so. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Use water spray to reduce vapours.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

For personal protection, see Section 8. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Keep unnecessary and unprotected personnel away from the spillage. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours. Avoid contact with skin, eyes and clothing. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains and the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Contain spillage with sand, earth or other suitable non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Dispose of contents/container in accordance with national regulations. Wash thoroughly after dealing with a spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Provide adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapour/spray. Avoid

the formation of mists. Use only non-sparking tools.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash skin thoroughly after handling. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep container tightly closed, in a cool, well ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight.

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Dimethyl ether

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

Acetone

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

WEL = Workplace Exposure Limit

Dimethyl ether (CAS: 115-10-6)

DNEL Workers - Inhalation; Long term systemic effects: 1894 mg/m³

General population - Inhalation; Long term systemic effects: 471 mg/m³

PNEC - Fresh water; 0.155 mg/l

- Marine water; 0.016 mg/l

- Intermittent release; 1.549 mg/l

- STP; 160 mg/l

Sediment (Freshwater); 0.681 mg/kgSediment (Marinewater); 0.069 mg/kg

- Soil; 0.045 mg/kg

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

DNEL Workers - Inhalation; Long term systemic effects: 2035 mg/m³

Workers - Dermal; Long term systemic effects: 773 mg/kg/day

General population - Inhalation; Long term systemic effects: 608 mg/kg/day General population - Dermal; Long term systemic effects: 699 mg/kg/day General population - Oral; Long term systemic effects: 699 mg/kg/day

Acetone (CAS: 67-64-1)

DNEL Workers - Inhalation; Long term systemic effects: 1210 mg/m³

Workers - Inhalation; Short term local effects: 2420 mg/m³ Workers - Dermal; Long term systemic effects: 186 mg/kg/day

General population - Inhalation; Long term systemic effects: 200 mg/m³ General population - Dermal; Long term systemic effects: 62 mg/kg/day General population - Oral; Long term systemic effects: 62 mg/kg/day

PNEC - Fresh water; 10.6 mg/l

Marine water; 1.06 mg/lIntermittent release; 21 mg/l

- STP; 100 mg/l

Sediment (Freshwater); 30.4 mg/kgSediment (Marinewater); 3.04 mg/kg

- Soil; 29.5 mg/kg

Resin acids and Rosin acids, esters with pentaerythritol (CAS: 8050-26-8)

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

DNEL Workers - Inhalation; Long term systemic effects: 44.6 mg/m³

Workers - Dermal; Long term systemic effects: 6.3 mg/kg/day

General population - Inhalation; Long term systemic effects: 13.2 mg/m³ General population - Dermal; Long term systemic effects: 3.8 mg/kg/day General population - Oral; Long term systemic effects: 3.8 mg/kg/day

PNEC - Fresh water; 0.027 mg/l

- Marine water; 0.003 mg/l - Intermittent release; 0.27 mg/l

- STP; 2 mg/l

Sediment (Freshwater); 625.79 mg/kgSediment (Marinewater); 62.58 mg/kg

- Soil; 125 mg/kg

Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS: 6683-19-8)

DNEL Workers - Inhalation; Long term systemic effects: 9.5 mg/m³

Workers - Dermal; Long term systemic effects: 27 mg/kg/day

General population - Inhalation; Long term systemic effects: 2.3 mg/m³ General population - Dermal; Long term systemic effects: 13.5 mg/kg/day General population - Oral; Long term systemic effects: 1.4 mg/kg/day

PNEC - Fresh water; 0.04 mg/l

- Marine water; 0.004 mg/l - Intermittent release; 0.86 mg/l

- STP; 1 mg/l

Sediment (Freshwater); 4000000 mg/kgSediment (Marinewater); 400000 mg/kg

- Soil; 798000 mg/kg

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Eye/face protection

Chemical splash goggles or face shield. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Wash skin thoroughly after handling. Take off contaminated clothing and wash it before reuse.

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Organic vapour + dust

and mist filter.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Not available.

Odour Characteristic.

Odour threshold Not available.

pH Not available.

Melting point Not available.

Initial boiling point and range 55°C @ 1013 hPa

Flash point -29°C

Evaporation factor Not available.

Flammability (solid, gas) Extremely flammable aerosol.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 1.0% Upper flammable/explosive limit: 13%

Vapour pressure Not available.

Vapour density Not available.

Relative density 0.74

Bulk density Not available.

Solubility(ies) Insoluble in water.

Partition coefficient Not available.

Auto-ignition temperature 275°C

Decomposition Temperature Not available.

Viscosity Not determined.

Explosive properties Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information None.

Volatile organic compound This product contains a maximum VOC content of 523 g/l.

SECTION 10: Stability and reactivity

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

12

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames

and other sources of ignition. Static electricity and formation of sparks must be prevented.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition

products

reactions

None at ambient temperatures. Thermal decomposition or combustion products may include

the following substances: Very toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not relevant.

Inhalation Coughing, chest tightness, feeling of chest pressure.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal

tract.

Skin contact Bonds skin and eyes in seconds. May cause skin irritation.

Eye contact Irritation of eyes and mucous membranes.

Toxicological information on ingredients.

Dimethyl ether

Acute toxicity - inhalation

Acute toxicity inhalation

164,000.0

(LC₅₀ gases ppmV)

Species Rat

ATE inhalation (gases

ppm)

164,000.0

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

Genotoxicity - in vivo Genome mutation: Negative.

Carcinogenicity

development

Carcinogenicity NOAEL 2.5 %, Inhalation, Rat

Reproductive toxicity

Reproductive toxicity -

y -

Developmental toxicity: - NOAEL: 40000 ppm, Inhalation, Rat

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 2.5 %, Inhalation, Rat

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

Acute toxicity - oral

Acute toxicity oral (LD50

5,840.0

mg/kg)

Species Rat

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Acute toxicity dermal (LD₅₀ 2,800.0

mg/kg)

Species Rat

ATE dermal (mg/kg) 2,800.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀: >25.2 mg/l, Inhalation, Vapour, Rat 4 hours

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Very slight erythema - barely

perceptible (1). Primary dermal irritation index: 0.67 Oedema score: No oedema (0).

Irritating.

Serious eye damage/irritation

Serious eye Dose: 0.2 ml, 7 days, Rabbit Not irritating.

damage/irritation

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroBacterial reverse mutation test: Negative. Read-across data.

Reproductive toxicity

Reproductive toxicity -

fertility

Two-generation study - NOAEL 31680 mg/m³, Inhalation, Rat P

Reproductive toxicity -

development

.

Developmental toxicity: - NOAEC: > 7000 ppm, Inhalation, Rabbit Read-across

data.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC 14000 mg/m³, Inhalation, Rat

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

Acetone

Acute toxicity - oral

Notes (oral LD₅o) LD₅o 5800 mg/kg, Oral, Rat REACH dossier information.

Acute toxicity - dermal

Notes (dermal LD₅o) LD₅o >15800 mg/kg, Dermal, Rabbit REACH dossier information.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ ~132 mg/l, Inhalation, Rat REACH dossier information.

Skin corrosion/irritation

Animal data Dose: 10 µl, 3 days, Guinea pig Erythema/eschar score: No erythema (0). Oedema

score: No oedema (0).

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Serious eye damage/irritation

Serious eye Causes serious eye irritation.

damage/irritation

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity NOEL 79 mg, Inhalation, Mouse

Reproductive toxicity

Reproductive toxicity -

Maternal toxicity: - NOAEC: 2200 ppm, Inhalation, Rat

development

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 50000 ppm, Oral, Rat

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >1-10 mg/l, Fish

Acute toxicity - LC₅₀, 96 hours: >1-10 mg/l, Algae

microorganisms

Ecological information on ingredients.

Dimethyl ether

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 4100 mg/l, Poecilia reticulata (Guppy)

NOEC, 96 hours: ≥ 4100 mg/l, Poecilia reticulata (Guppy)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: > 4400 mg/l, Daphnia magna NOEC, 48 hours: ≥ 4400 mg/l, Daphnia magna

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 72 hours: 10 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EL50, 48 hours: 3 mg/l, Daphnia magna

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Acute toxicity - aquatic

plants

EL50, 72 hours: 10-30 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

Chronic toxicity - fish early NOELR, 28 days: 2.045 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 0.17 mg/l, Daphnia magna LOEC, 21 days: 0.32 mg/l, Daphnia magna EC₅₀, 21 days: 0.23 mg/l, Daphnia magna

Acetone

Acute aquatic toxicity

LC₅₀, 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout) Acute toxicity - fish

Acute toxicity - aquatic

invertebrates

LC₅₀, 48 hours: 8800 mg/l, Daphnia pulex

Acute toxicity -

microorganisms

EC₅₀, 30 minutes: 61150 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

NOEC, 28 days: 2212 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be slowly biodegradable.

Ecological information on ingredients.

Dimethyl ether

Biodegradation Water - Degradation (5%): 28 days

No biodegradation observed under test conditions.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

Biodegradation Water - Degradation (83%): 16 days

> Water - Degradation (98%): 28 days The substance is readily biodegradable.

> > Acetone

Phototransformation Air - DT₅₀: ~ 10 days

Water - Degradation (100%): 4 days Biodegradation

The substance is readily biodegradable.

12.3. Bioaccumulative potential

No data available on bioaccumulation. Bioaccumulative potential

Partition coefficient Not available.

Ecological information on ingredients.

Dimethyl ether

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Partition coefficient log Pow: 0.07

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

Bioaccumulative potential No data available on bioaccumulation.

Acetone

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: -0.24

12.4. Mobility in soil

Mobility Semi-mobile. The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

Dimethyl ether

Mobility The product is soluble in water.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

Mobility The product has poor water-solubility.

Surface tension 20.9 mN/m @ 25°C

Acetone

Mobility The product is soluble in water.

Henry's law constant 3 Pa m³/mol @ 25°C

Surface tension 23 mN/m @ 20 - 25°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

Dimethyl ether

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

Acetone

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects None known.

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Empty containers must not be punctured or incinerated because of the risk of an explosion.

Disposal methods Do not empty into drains. Collect and place in suitable waste disposal containers and seal

securely. Dispose of contents/container in accordance with national regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3501
UN No. (IMDG) 3501
UN No. (ICAO) 3501
UN No. (ADN) 3501

14.2. UN proper shipping name

Proper shipping name

CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER)

(ADR/RID)

Proper shipping name (IMDG) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER)

Proper shipping name (ICAO) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER)

Proper shipping name (ADN) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER)

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 8F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Emergency Action Code 2YE

Hazard Identification Number 23

(ADR/RID)

Tunnel restriction code (B/D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978.

ATE: Acute Toxicity Estimate.

LC₅: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Kow: Octanol-water partition coefficient.

EC₅₀: 50% of maximal Effective Concentration.

Classification abbreviations

and acronyms

Aerosol = Aerosol

Skin Irrit. = Skin irritation

STOT SE = Specific target organ toxicity-single exposure

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

TENSORGRIP F60 NC HIGH GRAB FOAM AND FABRIC ADHESIVE CANISTER

Classification procedures according to Regulation (EC)

Aerosol 1 - H222, H229: Expert judgement. Skin Irrit. 2 - H315, STOT SE 3 - H336, Aquatic

Chronic 2 - H411: Calculation method.

1272/2008

Revision date 14/02/2018

Revision 12

Supersedes date 01/08/2017

SDS number 20720

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

DIRECTIONS FOR USE

PRODUCT LOGO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.