

SAFETY DATA SHEET TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

UFI: 2S1T-K1G9-T00A-KFAU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier QUIN GLOBAL BV LTD

De Droogmakerij 1851 LX Heiloo The Netherlands 0031 72 520 66 97

technicalhelp.uk@quinglobal.com

Manufacturer QUIN GLOBAL (UK) LTD

PO BOX 7634 PERTH PH2 1GA

Quin - 01738 501 510

technicalhelp.uk@quinglobal.com

1.4. Emergency telephone number

Emergency telephone QUIN - +44 (0) 1738 501 510 (24 hrs)

National emergency telephone For the emergency services - the ambulance, police and fire services - Tel: 999 / **number**When you need medical advice or treatment but it is not an emergency - Tel: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 3 - H229 Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms







Signal word Danger

Hazard statements H229 Pressurised container: may burst if heated.

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Additional information For professional users only.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Contains METHYL ACETATE, n-heptane

Supplementary precautionary

P261 Avoid breathing spray.

statements

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHYL ACETATE 60-100%

CAS number: 79-20-9 EC number: 201-185-2 REACH registration number: 01-

2119459211-47-XXXX

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

n-heptane 1-5%

CAS number: 142-82-5 EC number: 205-563-8 REACH registration number: 01-

2119457603-38-XXXX

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Stop if the affected person

feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take

place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin contact Remove contamination with soap and water or recognised skin cleansing agent. Continue to

rinse for at least 15 minutes. If adhesive bonding occurs, do not force skin apart.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention. If

adhesive bonding occurs, do not force eyelids apart.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. Wash

contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. During application and drying, solvent vapours will be emitted. Vapours in high

concentrations are narcotic.

Ingestion May cause stomach pain or vomiting. May cause drowsiness or dizziness.

Skin contact Redness. May be slightly irritating to skin. Bonds skin and eyes in seconds.

Eye contact Irritating to eyes. Bonds skin and eyes in seconds.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

> Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and

propellant. Vapours may form explosive mixtures with air.

Hazardous combustion products

Thermal decomposition or combustion products may include the following substances:

Carbon dioxide (CO2). Carbon monoxide (CO). Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs,

notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

6.2. Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the **Environmental precautions**

aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution

occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush away spillage with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

For professional users only. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store at temperatures between 10°C and 25°C. Store away from incompatible materials (see Section 10). Store in accordance with national regulations. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed and in a well-ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class

Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

METHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 616 mg/m³ Short-term exposure limit (15-minute): WEL 250 ppm 770 mg/m³

n-heptane

Long-term exposure limit (8-hour TWA): WEL 500 ppm 2085 mg/m³ WEL = Workplace Exposure Limit.

METHYL ACETATE (CAS: 79-20-9)

DNEL Workers - Inhalation; Long term systemic effects: 610 mg/m³

Workers - Inhalation; Long term local effects: 305 mg/m³ Workers - Dermal; Long term systemic effects: 88 mg/kg/day

General population - Inhalation; Long term systemic effects: 131 mg/m³ General population - Inhalation; Long term local effects: 152 mg/m³ General population - Dermal; Long term systemic effects: 44 mg/kg/day General population - Oral; Long term systemic effects: 44 mg/kg/day

PNEC - Fresh water; 0.12 mg/l

marine water; 0.012 mg/lIntermittent release; 1.2 mg/l

- STP; 600 mg/l

Sediment (Freshwater); 0.128 mg/kgSediment (Marinewater); 0.013 mg/kg

- Soil; 20.4 mg/kg

n-heptane (CAS: 142-82-5)

DNEL Workers - Inhalation; Long term systemic effects: 2085 mg/m³

Workers - Dermal; Long term systemic effects: 300 mg/kg/day

General population - Inhalation; Long term systemic effects: 447 mg/m³ General population - Dermal; Long term systemic effects: 149 mg/kg/day General population - Oral; Long term systemic effects: 149 mg/kg/day

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure the ventilation system is regularly maintained and tested. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard

should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be

allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried

out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with

replaceable filter cartridges should comply with European Standard EN140.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Orange.

Odour Characteristic.

Odour threshold Not available.

pH Not available.

Melting point Not available.

Initial boiling point and range 57°C @ 1013 hPa

Flash point -10°C

Evaporation rate Not available.

Evaporation factor Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 2.5 g/100 g Upper flammable/explosive limit: 13 g/100 g

Vapour pressure Not available.

Vapour density Not available.

Relative density 0.9

Solubility(ies) Insoluble in water.

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

Partition coefficient Not available.

540°C **Auto-ignition temperature**

Not available. **Decomposition Temperature** Viscosity Not available.

Explosive properties Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of <80 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidising agents.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Containers can

burst violently or explode when heated, due to excessive pressure build-up.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Thermal decomposition or combustion products may include the following substances: Acrid

products

smoke or fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD50) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD50) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Based on available data the classification criteria are not met. Notes (inhalation LC₅₀)

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, disziness, disorientation, vertigo. Narcotic effect. During application and drying, solvent vapours will be emitted. Vapours in high

concentrations are narcotic.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Redness. May be slightly irritating to skin. Bonds skin and eyes in seconds.

Eye contact Irritating to eyes. Bonds skin and eyes in seconds.

Toxicological information on ingredients.

METHYL ACETATE

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀: > 2000 mg/kg, Dermal, Rat

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema

score: No oedema (0). Not irritating.

Serious eye damage/irritation

Serious eye Dose: 0.1 ml, 1 - 72 hours, Rabbit Irritating.

damage/irritation

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Human: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

Genotoxicity - in vivo Chromosome aberration: Negative.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Resin acids and Rosin acids, esters with pentaerythritol

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀: > 2000 mg/kg, Dermal, Rat

Skin corrosion/irritation

Animal data Dose: 0.5 g, 4 hours, Rabbit Primary dermal irritation index: 0.1 Fully reversible

within 48 hours. Not irritating.

Serious eye damage/irritation

Serious eye

damage/irritation

Dose: 100 mg, 7 days, Rabbit Not irritating.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroBacterial reverse mutation test: Negative.

Reproductive toxicity

Reproductive toxicity -

fertility

Screening - NOAEL 20000 ppm, Oral, Rat P, F1

n-heptane

Acute toxicity - oral

Notes (oral LD₅o) LD₅o : > 5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ : > 2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ : > 29.29 mg/l, Inhalation, Vapour, Rat

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: Very slight erythema -

barely perceptible (1). Oedema score: No oedema (0). Primary dermal irritation

index: 0.25 Irritating.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.

Reproductive toxicity

Reproductive toxicity - Two-generation study - NOAEL 31680 mg/m³, Inhalation, Rat P

fertility

Specific target organ toxicity - single exposure

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC 12470 mg/m³, Inhalation, Rat

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

METHYL ACETATE

Acute aquatic toxicity

Acute toxicity - fish LC₀, 48 hours: 250 mg/l, Brachydanio rerio (Zebra Fish)

LC₅₀, 48 hours: 250 - 350 mg/l, Brachydanio rerio (Zebra Fish) LC₁₀₀, 48 hours: 500 mg/l, Brachydanio rerio (Zebra Fish) LC₀, 96 hours: 250 mg/l, Brachydanio rerio (Zebra Fish) LC₅₀, 96 hours: 250 - 350 mg/l, Brachydanio rerio (Zebra Fish) LC₁₀₀, 96 hours: 500 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 362 mg/l, Daphnia magna EC₅₀, 48 hours: 1026.7 mg/l, Daphnia magna EC₁₀₀, 48 hours: 1448.2 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: > 120 mg/l, Desmodesmus subspicatus EC₁₀₀, 72 hours: > 100 mg/l, Desmodesmus subspicatus NOEC, 72 hours: 120 mg/l, Desmodesmus subspicatus

Acute toxicity - microorganisms

EC₅₀, 16 hours: 6000 mg/l, Pseudomonas putida

Resin acids and Rosin acids, esters with pentaerythritol

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 1000 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - microorganisms

NOEC, 28 days: 20 mg/l, Activated sludge

n-heptane

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute)

Acute toxicity - fish LL₅₀, 96 hours: 5.738 mg/l, Oncorhynchus mykiss (Rainbow trout)

Calculation method.

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1.5 mg/l, Daphnia magna

Chronic aquatic toxicity

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

M factor (Chronic) 1

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 0.17 mg/l, Daphnia magna LOEC, 21 days: 0.32 mg/l, Daphnia magna EC₅₀, 21 days: 0.23 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

METHYL ACETATE

Phototransformation Air - DT₅₀ : 50.4 days

Biodegradation Water - Degradation (70%): 28 days

The substance is readily biodegradable.

n-heptane

Phototransformation Air - DT₅₀: 4.5 days

Biodegradation Water - Degradation (70%): 10 days

The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Resin acids and Rosin acids, esters with pentaerythritol

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 3.31

Nitrogen

Partition coefficient log Pow: 8.08

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Ecological information on ingredients.

METHYL ACETATE

Adsorption/desorption

coefficient

Water - Log Koc: 0.18 @ 40°C

Henry's law constant 6.43 Pa m³/mol @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvBThis product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

METHYL ACETATE

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

Resin acids and Rosin acids, esters with pentaerythritol

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

n-heptane

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Disposal of this product, process solutions, residues and by-products should at all times

comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. The generation of waste should be minimised or avoided wherever possible. When handling waste, the safety

precautions applying to handling of the product should be considered.

Disposal methodsDo not empty into drains. Care should be taken when handling emptied containers that have

not been thoroughly cleaned or rinsed out. Dispose of contents/container in accordance with

national regulations.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3501

UN No. (IMDG) 3501

UN No. (ICAO) 3501

UN No. (ADN) 3501

14.2. UN proper shipping name

Proper shipping name CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (METHYL ACETATE,

(ADR/RID) COMPRESSED GAS)

Proper shipping name (IMDG) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (METHYL ACETATE,

COMPRESSED GAS)

Proper shipping name (ICAO) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (METHYL ACETATE,

COMPRESSED GAS)

Proper shipping name (ADN) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (METHYL ACETATE,

COMPRESSED GAS)

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 8F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

No information required.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

2 ADR transport category

Emergency Action Code 2YE

Hazard Identification Number 23

(ADR/RID)

Tunnel restriction code (B/D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to No information required.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

TENSORGRIP LP64 SPRAY CONTACT ADHESIVE CANISTER

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC50: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Aerosol = Aerosol Eye Irrit. = Eye irritation

STOT SE = Specific target organ toxicity-single exposure

Aguatic Chronic = Hazardous to the aguatic environment (chronic)

Classification procedures according to Regulation (EC)

1272/2008

Aerosol 1 - H222, H229: Expert judgement. Eye Irrit. 2 - H319, STOT SE 3 - H336, Aquatic

Chronic 2 - H411: Calculation method.

Revision date 07/01/2021

Revision 21

Supersedes date 02/12/2020

SDS number 20190

Hazard statements in full H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

DIRECTIONS FOR USE

PRODUCT LOGO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.