

SAFETY DATA SHEET Woodstikk UF Veneering Kit Part B (Hot Press)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Woodstikk UF Veneering Kit Part B (Hot Press)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener. Wood adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier UREKA GLOBAL LTD

7 FLOWERS HILL, BRISLINGTON BRISTOL

BS4 5JJ

+44 117 971 1364

sales@thenamethatsticks.com

1.4. Emergency telephone number

Emergency telephone Ureka Global +44 (0)117 971 1364 (Mon - Fri) 09:00 - 16:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

AMMONIUM CHLORIDE 1-5%

CAS number: 12125-02-9 EC number: 235-186-4

Classification

Acute Tox. 4 - H302 Eye Irrit. 2 - H319

The full text for all hazard statements is displayed in Section 16.

Composition comments Contains: Calcium Sulphate CAS 7778-18-9; Maize Starch CAS 9005-25-8; Diammonium

Hydrogen Phosphate CAS 7783-28-0

Woodstikk UF Veneering Kit Part B (Hot Press)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once. Place unconscious person on their side in the

recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Move affected person to fresh air and keep warm and at rest in a position

comfortable for breathing.

Inhalation Move affected person to fresh air at once. Get medical attention if symptoms are severe or

persist. Development of symptoms may be delayed for 24 to 48 hours.

Ingestion Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Give milk instead of water if readily available. Get medical attention if symptoms are severe or

persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention promptly if symptoms occur after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes. Get medical attention if irritation persists after

washing

Protection of first aidersNo action should be taken involving any personal risk without suitable training.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Dust is severely irritating to the upper respiratory system. Coughing.

Ingestion No known chronic or acute health risks.

Skin contact No specific symptoms known.

Eye contact Irritation. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Development of symptoms may be delayed for 24 to 48 hours.

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Alcohol resistant foam. Water spray, fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Dust may form explosive mixture with air.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Carbon dioxide (CO2). Carbon monoxide (CO). Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during

firefighting

Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

Woodstikk UF Veneering Kit Part B (Hot Press)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Evacuate unnecessary personnel.

For emergency responders Wear personal protective equipment as described in section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant

authorities if the product has caused environmental pollution.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Move containers from spillage area. Eliminate all sources of ignition. Collect powder using

special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal

containers and seal securely. Avoid generation and spreading of dust.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Avoid breathing dust. Provide adequate ventilation. Use explosion-proof electrical, ventilating and lighting equipment. Take precautionary measures

against static discharge.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective

equipment before entering eating area.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from the following materials: Oxidising materials. Store in a dry place. Keep

container tightly sealed when not in use. Keep away from food, drink and animal feeding

stuffs.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

AMMONIUM CHLORIDE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ Short-term exposure limit (15-minute): WEL 20 mg/m³

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Use explosion-proof general and local exhaust ventilation.

Woodstikk UF Veneering Kit Part B (Hot Press)

Eye/face protection Chemical splash goggles.

Hand protection Chemical resistant protective gloves (EN374)

Other skin and body

protection

Wear appropriate clothing to prevent skin contamination.

Hygiene measuresWash at the end of each work shift and before eating, smoking and using the toilet. Provide

eyewash station and safety shower. Take off contaminated clothing and wash it before reuse.

Respiratory protection Particulate filters should comply with European Standard EN143.

Environmental exposure

Emissions from ventilation or work process equipment should be checked to ensure they

controls comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Solid. Powder

Colour Off-white.

Odour Odourless.

Soluble in water.

Oxidising properties No chemical group associated with oxidising properties

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

ReactivityNo test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid generation and spreading of dust. Avoid dust close to ignition sources. Static electricity

and formation of sparks must be prevented.

10.5. Incompatible materials

Materials to avoid Oxidising materials.

10.6. Hazardous decomposition products

Hazardous decomposition

No known hazardous decomposition products.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 50,000.0

SECTION 12: Ecological information

Woodstikk UF Veneering Kit Part B (Hot Press)

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methodsDispose in a safe manner in accordance with local/national regulations.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Woodstikk UF Veneering Kit Part B (Hot Press)

SECTION 16: Other information

Issued by Compliance Manager

Revision date 29/07/2021

Revision 1

SDS number 24615

Hazard statements in full H302 Harmful if swallowed.

H319 Causes serious eye irritation.

DIRECTIONS FOR USE

PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.