



SAFETY DATA SHEET

Woodstikk UF Veneering Kit Part B (Slow/Summer)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Woodstikk UF Veneering Kit Part B (Slow/Summer)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener. Wood adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier UREKA GLOBAL LTD
7 FLOWERS HILL,
BRISLINGTON
BRISTOL
BS4 5JJ
+44 117 971 1364
sales@thenamesthatsticks.com

1.4. Emergency telephone number

Emergency telephone UREKA GLOBAL LTD: +44 (0) 117 971 1364

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/ attention.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Woodstikk UF Veneering Kit Part B (Slow/Summer)

AMMONIUM CHLORIDE	10-25%
CAS number: 12125-02-9	EC number: 235-186-4
Classification Acute Tox. 4 - H302 Eye Irrit. 2 - H319	

The full text for all hazard statements is displayed in Section 16.

Composition comments Contains Kaolin (China Clay) CAS 1332-58-7 Contains Urea CAS 57-13-6

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Place unconscious person on their side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	Move affected person to fresh air at once. Get medical attention if symptoms are severe or persist. Development of symptoms may be delayed for 24 to 48 hours.
Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Give plenty of water to drink. Get medical attention if symptoms are severe or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if irritation persists after washing.
Protection of first aiders	No action should be taken involving any personal risk without suitable training.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Dust is severely irritating to the upper respiratory system. May cause respiratory irritation. Coughing.
Ingestion	No known chronic or acute health risks.
Skin contact	No specific symptoms known.
Eye contact	Irritating to eyes. Irritation. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Development of symptoms may be delayed for 24 to 48 hours.
Specific treatments	No specific first aid measures noted. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Alcohol resistant foam. Water spray, fog or mist.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Dust may form explosive mixture with air.
-------------------------	---

Woodstikk UF Veneering Kit Part B (Slow/Summer)

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Move containers from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders Wear personal protective equipment as described in section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Avoid generation and spreading of dust. Move containers from spillage area.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid breathing dust. Provide adequate ventilation. Use explosion-proof electrical, ventilating and lighting equipment. Take precautionary measures against static discharge.

Advice on general occupational hygiene Do not eat, drink or smoke while working. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating area.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from other materials. Store away from the following materials: Oxidising materials. Keep container tightly closed and dry. Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

AMMONIUM CHLORIDE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

Short-term exposure limit (15-minute): WEL 20 mg/m³

WEL = Workplace Exposure Limit.

Woodstikk UF Veneering Kit Part B (Slow/Summer)

8.2. Exposure controls

Protective equipment



Eye/face protection

Wear tight-fitting, dust-resistant, chemical splash goggles if airborne dust is generated.

Hand protection

Wear protective gloves. Chemical resistant protective gloves (EN374)

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Take off immediately all contaminated clothing and wash it before reuse. Eye wash facilities and emergency shower must be available when handling this product.

Respiratory protection

Particulate filters should comply with European Standard EN143.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid. Powder
Colour	Off-white.
Odour	No characteristic odour.
Solubility(ies)	Soluble in water.
Explosive properties	Dust may form explosive mixture with air.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Avoid generation and spreading of dust. Avoid dust close to ignition sources. Avoid the accumulation of dust. Static electricity and formation of sparks must be prevented.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Oxidising materials.
--------------------	----------------------

10.6. Hazardous decomposition products

Woodstikk UF Veneering Kit Part B (Slow/Summer)

Hazardous decomposition products No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 5,000.0

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose in a safe manner in accordance with local/national regulations.

Waste class The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Woodstikk UF Veneering Kit Part B (Slow/Summer)

Transport in bulk according to Not applicable.
Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by	Compliance Manager
Revision date	29/07/2021
Revision	1
SDS number	24610
Hazard statements in full	H302 Harmful if swallowed. H319 Causes serious eye irritation.

DIRECTIONS FOR USE

PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.