



SAFETY DATA SHEET

Woodstikk UF Filler Extender

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Woodstikk UF Filler Extender

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wood adhesive. Hardener.

1.3. Details of the supplier of the safety data sheet

Supplier UREKA GLOBAL LTD
7 FLOWERS HILL,
BRISLINGTON
BRISTOL
BS4 5JJ
+44 117 971 1364
sales@thenamesthatsticks.com

1.4. Emergency telephone number

Emergency telephone Ureka Global +44 (0)117 971 1364 (Mon - Fri) 09:00 - 16:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Composition comments Contains: Calcium Sulphate, CAS 7778-18-9, 30-60%; Maize Starch, CAS 9005-25-8, 10-30%; Kaolin, CAS 1332-58-7, 10-30%.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Inhalation Move affected person to fresh air at once. Get medical attention if symptoms are severe or persist. Development of symptoms may be delayed for 24 to 48 hours.

Woodstikk UF Filler Extender

Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Give plenty of water to drink. Get medical attention if symptoms are severe or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if irritation persists after washing.
Protection of first aiders	No action should be taken involving any personal risk without suitable training.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Dust is severely irritating to the upper respiratory system. Coughing. May cause respiratory irritation.
Ingestion	No known chronic or acute health risks.
Skin contact	No specific symptoms known.
Eye contact	Irritating to eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Development of symptoms may be delayed for 24 to 48 hours.
Specific treatments	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, fog or mist. Alcohol-resistant foam.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Dust may form explosive mixture with air. Take precautionary measures against static discharge.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO). Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting	Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Move containers from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of dust. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.
-----------------------------	--

Woodstikk UF Filler Extender

For emergency responders Wear personal protective equipment as described in section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Move containers from spillage area. Eliminate all sources of ignition. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Avoid generation and spreading of dust.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing. Avoid breathing dust. Provide adequate ventilation. Take precautionary measures against static discharge.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from other materials. Eliminate ignition sources. Keep away from oxidising materials, heat and flames. Keep container tightly sealed when not in use. Store in a dry place. Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Maize Starch: Long-term exposure limit (8 hour TWA): 10mg/m³, inhalable dust.

Long-term exposure limit (8 hour TWA): WEL 4 mg/m³, respirable dust.

Kaolin: long-term exposure limit (8 hour TWA): WEL 2 mg/m³, respirable dust.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, dust-resistant, chemical splash goggles if airborne dust is generated.

Hand protection

Chemical resistant protective gloves (EN374)

Other skin and body protection

Wear appropriate clothing to prevent skin contamination. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Woodstikk UF Filler Extender

Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Wash contaminated clothing before reuse. Eye wash facilities and emergency shower must be available when handling this product.
Respiratory protection	Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Particulate filters should comply with European Standard EN143.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid. Powder.
Colour	Off-white.
Odour	No characteristic odour.
Solubility(ies)	Soluble in water.
Explosive properties	Dust may form explosive mixture with air.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid generation and spreading of dust. Avoid dust close to ignition sources. Static electricity and formation of sparks must be prevented.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Oxidising materials.
---------------------------	----------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	No known hazardous decomposition products.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 1970 mg/l, Fish
------------------------------	--

Woodstikk UF Filler Extender

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

General Not regulated for road, rail, inland waterways, sea or air transport.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
Control of Substances Hazardous to Health Regulations 2002 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Compliance Manager

Revision date 16/09/2021

Revision 1

SDS number 24703

DIRECTIONS FOR USE

PRODUCT LOGO

Woodstikk UF Filler Extender

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.