



Safety Data Sheet

Copyright, 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	05-8564-6	Version number:	24.00
Revision date:	23/01/2020	Supersedes date:	16/01/2019
Transportation version number: 6.00 (09/08/2015)			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld(TM) Universal Adhesive 847

Product Identification Numbers

FS-9100-0583-4 FS-9100-0633-7

7000079819 7000079823

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements**CLP REGULATION (EC) No 1272/2008****SIGNAL WORD**

DANGER.

Symbols:

GHS02 (Flame) | GHS07 (Exclamation mark) |

Pictograms**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
acetone	67-64-1	200-662-2	60 - 70

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapours.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H412	Harmful to aquatic life with long lasting effects.
------	--

No precautionary statements are required for containers <=125 mL.

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Contains 8% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
acetone	67-64-1	200-662-2	01- 2119471330- 49	60 - 70	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066
Acrylonitrile - butadiene polymer	9003-18-3			10 - 20	Substance not classified as hazardous
Resin acids and rosin acids, esters with glycerol	8050-31-5	232-482-5		5 - 10	Substance not classified as hazardous
Phenol-formaldehyde resin	Trade Secret			1 - 10	Substance not classified as hazardous
salicylic acid	69-72-7	200-712-3	01- 2119486984- 17	< 3	Acute Tox. 4, H302; Eye Dam. 1, H318; Repr. 2, H361d
zinc oxide	1314-13-2	215-222-5	01- 2119463881- 32	< 2.5	Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	270-128-1		< 0.5	Aquatic Acute 1, H400,M=1
4-tert-butylphenol	98-54-4	202-679-0	01- 2119489419- 21	< 0.5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Repr. 2, H361f; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Ketones.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
acetone	67-64-1	UK HSC	TWA:1210 mg/m ³ (500 ppm);STEL:3620 mg/m ³ (1500 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
salicylic acid		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	2 mg/kg bw/d
salicylic acid		Worker	Inhalation, Long-term exposure (8 hours), Local effects	1 mg/m ³
salicylic acid		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	16 mg/m ³

salicylic acid		Worker	Inhalation, Short-term exposure, Local effects	3 mg/m ³
zinc oxide		Worker	Dermal, Long-term exposure (8 hours), Local effects	622 mg/cm ²
zinc oxide		Worker	Dermal, Short-term exposure, Local effects	6,223 mg/cm ²
zinc oxide		Worker	Inhalation, Long-term exposure (8 hours), Local effects	1.2 mg/m ³
zinc oxide		Worker	Inhalation, Short-term exposure, Local effects	6.2 mg/m ³
zinc oxide		Worker	Oral, Short-term exposure, Local effects	62.2 mg/kg bw/d

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
salicylic acid		Agricultural soil	0.17 mg/kg d.w.
salicylic acid		Freshwater	0.2 mg/l
salicylic acid		Freshwater sediments	1.42 mg/kg d.w.
salicylic acid		Marine water	0.02 mg/l
salicylic acid		Marine water sediments	0.14 mg/kg d.w.
salicylic acid		Sewage Treatment Plant	162 mg/l
zinc oxide		Agricultural soil	44.3 mg/kg d.w.
zinc oxide		Freshwater	0.0256 mg/l
zinc oxide		Freshwater sediments	146 mg/kg d.w.
zinc oxide		Marine water	0.0076 mg/l
zinc oxide		Marine water sediments	70.3 mg/kg d.w.
zinc oxide		Sewage Treatment Plant	0.0647 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	No data available	No data available
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties**Appearance**

Physical state

Liquid.

Colour

Brown

Specific Physical Form:

Viscous.

Odor

acetone

Odour threshold

No data available.

pH

No data available.

Boiling point/boiling range

55.8 - 56.6 °C [*Details:* Acetone value]

Melting point

No data available.

Flammability (solid, gas)

Not applicable.

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

-17 °C [*Test Method:* Closed Cup]

Autoignition temperature

No data available.

Flammable Limits(LEL)

No data available.

Flammable Limits(UEL)

No data available.

Vapour pressure

No data available.

Relative density

0.87 - 0.9 [*Ref Std:* WATER=1]

Water solubility

Slight (less than 10%)

Solubility- non-water

No data available.

Partition coefficient: n-octanol/water

No data available.

Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	1,500 - 3,200 mPa-s [@ 25 °C]
Density	No data available.

9.2. Other information

EU Volatile Organic Compounds

No data available.

Percent volatile

approximately 65 % weight

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Prolonged or repeated exposure may cause:

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg
Acrylonitrile - butadiene polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile - butadiene polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Ingestion	Rat	LD50 > 2,000 mg/kg
Phenol-formaldehyde resin	Dermal		LD50 estimated to be > 5,000 mg/kg
Phenol-formaldehyde resin	Ingestion	Rat	LD50 5,660 mg/kg
salicylic acid	Dermal	Rat	LD50 > 2,000 mg/kg
salicylic acid	Ingestion	Rat	LD50 891 mg/kg
zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
4-tert-butylphenol	Dermal	Rabbit	LD50 2,318 mg/kg
4-tert-butylphenol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.6 mg/l
4-tert-butylphenol	Ingestion	Rat	LD50 4,000 mg/kg
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Dermal	Rat	LD50 > 2,000 mg/kg
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

acetone	Mouse	Minimal irritation
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Minimal irritation
salicylic acid	Rabbit	No significant irritation
zinc oxide	Human and animal	No significant irritation
4-tert-butylphenol	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
acetone	Rabbit	Severe irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Mild irritant
salicylic acid	Rabbit	Corrosive
zinc oxide	Rabbit	Mild irritant
4-tert-butylphenol	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Resin acids and rosin acids, esters with glycerol	Guinea pig	Not classified
Phenol-formaldehyde resin	Human	Some positive data exist, but the data are not sufficient for classification
salicylic acid	Mouse	Not classified
zinc oxide	Guinea pig	Not classified
4-tert-butylphenol	Human and animal	Not classified

Photosensitisation

Name	Species	Value
salicylic acid	Mouse	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Resin acids and rosin acids, esters with glycerol	In Vitro	Not mutagenic
salicylic acid	In Vitro	Not mutagenic
salicylic acid	In vivo	Not mutagenic
zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
4-tert-butylphenol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
acetone	Not specified.	Multiple animal species	Not carcinogenic
4-tert-butylphenol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
salicylic acid	Ingestion	Toxic to development	Rat	NOAEL 75 mg/kg/day	during organogenesis
zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
4-tert-butylphenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	Not classified for development	Rat	NOAEL 70 mg/kg/day	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
4-tert-butylphenol	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	LOAEL 5.6 mg/l	4 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks

acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Resin acids and rosin acids, esters with glycerol	Ingestion	liver heart skin endocrine system bone, teeth, nails, and/or hair blood bone marrow hematopoietic system immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 5,000 mg/kg/day	90 days
salicylic acid	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	3 days
zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
4-tert-butylphenol	Ingestion	endocrine system liver kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	blood	Not classified	Rat	NOAEL 200 mg/kg	6 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
----------	-------	----------	------	----------	---------------	-------------

3M Scotch-Weld(TM) Universal Adhesive 847

acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
acetone	67-64-1	Crustacea other	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acrylonitrile - butadiene polymer	9003-18-3		Data not available or insufficient for classification			
Resin acids and rosin acids, esters with glycerol	8050-31-5	Fathead minnow	Estimated	96 hours	Lethal Level 50%	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green Algae	Estimated	72 hours	Effect Level 50%	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green Algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
Phenol-formaldehyde resin	Trade Secret		Data not available or insufficient for classification			
salicylic acid	69-72-7	Green algae	Experimental	72 hours	EC50	>100 mg/l
salicylic acid	69-72-7	Ricefish	Experimental	96 hours	LC50	>100 mg/l
salicylic acid	69-72-7	Water flea	Experimental	48 hours	EC50	870 mg/l
salicylic acid	69-72-7	Water flea	Experimental	21 days	NOEC	10 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
zinc oxide	1314-13-2	Crustacea other	Experimental	24 hours	LC50	0.24 mg/l
zinc oxide	1314-13-2	Green Algae	Experimental	72 hours	EC50	0.057 mg/l
zinc oxide	1314-13-2	Algae or other aquatic plants	Estimated	96 hours	Effect Concentration 10%	0.026 mg/l
zinc oxide	1314-13-2	Crustacea other	Estimated	24 days	NOEC	0.007 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	30 days	NOEC	0.049 mg/l
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1	Water flea	Experimental	24 hours	EC50	0.82 mg/l
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1	Zebra Fish	Experimental	96 hours	LC50	>71 mg/l
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1	Green algae	Experimental	72 hours	NOEC	>10 mg/l
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1	Water flea	Experimental	21 days	Effect Concentration 10%	1.69 mg/l
4-tert-butylphenol	98-54-4	Crustacea other	Experimental	96 hours	LC50	1.9 mg/l

3M Scotch-Weld(TM) Universal Adhesive 847

4-tert-butylphenol	98-54-4	Green Algae	Experimental	72 hours	EC50	14 mg/l
4-tert-butylphenol	98-54-4	Ricefish	Experimental	96 hours	LC50	5.1 mg/l
4-tert-butylphenol	98-54-4	Water flea	Experimental	48 hours	EC50	3.9 mg/l
4-tert-butylphenol	98-54-4	Fathead minnow	Experimental	128 days	NOEC	0.01 mg/l
4-tert-butylphenol	98-54-4	Green Algae	Experimental	72 hours	NOEC	0.32 mg/l
4-tert-butylphenol	98-54-4	Water flea	Experimental	21 days	NOEC	0.73 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	Other methods
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 % weight	OECD 301D - Closed bottle test
Acrylonitrile - butadiene polymer	9003-18-3	Data not available - insufficient			N/A	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Phenol-formaldehyde resin	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THC O2 evolution	
salicylic acid	69-72-7	Experimental Biodegradation	14 days	BOD	88.1 % BOD/ThBOD	OECD 301C - MITI test (I)
zinc oxide	1314-13-2	Data not available - insufficient			N/A	
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Experimental Biodegradation	28 days	CO2 evolution	<=1 % weight	OECD 301B - Modified sturm or CO2
4-tert-butylphenol	98-54-4	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	98 % weight	Other methods

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	Other methods
Acrylonitrile - butadiene polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Resin acids and rosin acids, esters with glycerol	8050-31-5	Experimental Bioconcentration		Log Kow	<1.5	Other methods
Phenol-formaldehyde resin	Trade Secret	Estimated Bioconcentration		Bioaccumulation factor	7.4	Other methods
salicylic acid	69-72-7	Experimental Bioconcentration		Log Kow	2.26	Other methods
zinc oxide	1314-13-2	Experimental BCF- Carp	56 days	Bioaccumulation factor	≤217	OECD 305E - Bioaccumulation flow-through fish test
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Estimated BCF- Carp	42 days	Bioaccumulation factor	1730	Other methods
4-tert-butylphenol	98-54-4	Experimental BCF- Carp	56 days	Bioaccumulation factor	88	OECD 305E - Bioaccumulation flow-through fish test

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
acetone	67-64-1	0	

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

FS-9100-0583-4, FS-9100-0633-7

ADR/RID: UN1133, ADHESIVES, LIMITED QUANTITY, 3., II, (E), ADR Classification Code: F1.

IMDG-CODE: UN1133, ADHESIVES, 3., II, IMDG-Code segregation code: NONE, LIMITED QUANTITY, EMS: FE,SD.

ICAO/IATA: UN1133, ADHESIVES, 3., II.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Authorization status under REACH:**

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

Ingredient

4-tert-butylphenol

CAS Nbr

98-54-4

Authorization status: listed in the Candidate List of Substances of Very High Concern for Authorization

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Formulation: Section 16: Annex information was modified.

Industrial Use of Adhesives: Section 16: Annex information was modified.

Professional Use of Adhesives and Sealants: Section 16: Annex information was modified.

Professional Use of Adhesives: Section 16: Annex information was modified.

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 5: Hazardous combustion products table information was modified.

Section 8: DNEL table row information was modified.

Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 8: PNEC table row information was modified.

Section 09: Color information was added.

Section 09: Odor information was added.

Sections 3 and 9: Odour, colour, grade information information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Photosensitisation Table information was modified.

Section 11: Reproductive and/or Developmental Effects text information was deleted.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 15: Authorization status under REACH: SVHC Authorization ingredient information information was added.

Section 15: Regulations - Inventories information was deleted.

Section 16: UK disclaimer information was deleted.

Annex

1. Title	
Substance identification	zinc oxide; EC No. 215-222-5; CAS Nbr 1314-13-2;
Exposure Scenario Name	Formulation
Lifecycle Stage	Formulation or re-packing
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Open sampling. Transfer of substance/mixture with dedicated engineering controls. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Continuous release; Frequency of exposure at workplace [for one worker]: 8 hours/day; Used amount or applied quantity per task/application by worker: 50 tonnes per year;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Protective clothing / Wear suitable protective clothing; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: Waste Water treatment - Incineration;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator; Send to a municipal sewage treatment plant;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	salicylic acid; EC No. 200-712-3; CAS Nbr 69-72-7;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Uniform distribution with roller application.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions:

	Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 365 days/year; Indoors with good general ventilation; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Ensure that direct skin contact is avoided; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	zinc oxide; EC No. 215-222-5; CAS Nbr 1314-13-2;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 07 -Industrial spraying PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Can be applied by rolling or spraying.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Continuous release; Frequency of exposure at workplace [for one worker]: 8 hours/day; Used amount or applied quantity per task/application by worker: 50 tonnes per year;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Protective clothing / Wear suitable protective clothing; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator; Send to a municipal sewage treatment plant;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	zinc oxide; EC No. 215-222-5; CAS Nbr 1314-13-2;
Exposure Scenario Name	Professional Use of Adhesives
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Can be applied by rolling or spraying.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Continuous release; Frequency of exposure at workplace [for one worker]: 8 hours/day; Used amount or applied quantity per task/application by worker: 50 tonnes per year;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Protective clothing / Wear suitable protective clothing; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	salicylic acid; EC No. 200-712-3; CAS Nbr 69-72-7;
Exposure Scenario Name	Professional Use of Adhesives and Sealants
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 10 -Roller application or brushing ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Application with pump spray
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 365 days/year; Indoors with good general ventilation; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures:

	Human health: Ensure that direct skin contact is avoided; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk